


Sampling Pumps

Geotech Portable Bladder Pumps

Geotech's portable bladder pumps were designed with input from field technicians who actually do the sampling! Single turn release heads and quick change bladders have been incorporated for quick in-the-field bladder changes and easy decontamination. Custom hose barbs allow the pump to be suspended without the need for tubing clamps.

FEATURES

- **Constructed of 316 Stainless Steel**
For unsurpassed durability and truly representative samples
- **Portable turnkey systems available**
Everything you need to quickly and efficiently sample your site
- **Single turn release housings**
No special tools or training required to service the pump
- **Quick-change bladder configuration**
Bladders can be easily exchanged without tools by sliding back the Teflon® collars
- **Extra bladders are readily available**
Available in Teflon® and Polyethylene (1.66" pump only)
- **Bonded tubing**
In Polyethylene and Teflon® lined Polyethylene by the foot or by the roll
- **Compatible with the GeoControl Pro & Geocontroller II Logic Units**



SPECIFICATIONS

	1.66 Portable	.850 Portable	.675 Portable
Pump Housing	316 SS	316 SS	316 SS
Pump Ends	316 SS	316 SS	316 SS
Bladder Material	Virgin PTFE	Virgin PTFE	Virgin PTFE
Outer Diameter	1.66"	.850"	.675"
Length w/Screen	19"	18 5/8"	18 3/4"
Weight	3.0 lbs.	1.1 lbs.	.83 lbs.
Volume/Cycle	124 mL	74 mL	59 mL
Min. Well I.D.	2"	1"	.75"
Max. Operating Pressure	100 psi	100 psi	100 psi
Min. Operating Pressure	5 psi (ash)*	5 psi (ash)*	5 psi (ash)*
Maximum Sampling Depth	200'	200'	200'
Tubing Size			
Air	.17" ID x .25" OD	.17" ID x .25" OD	.17" ID x .25" OD
Discharge	.25" ID x .375" OD	.17" ID x .25" OD	.17" ID x .25" OD

*ash = above static head

CALL GEOTECH TODAY (800) 833-7958

Geotech Environmental Equipment, Inc.
2650 East 40th Avenue • Denver, Colorado 80205
(303) 320-4764 • **(800) 833-7958** • FAX (303) 322-7242
email: sales@geotechenv.com website: www.geotechenv.com